

Enhanced Asphalt Preservation with a Darker Finish

RePlay+ is an advanced formulation designed to extend the life of asphalt pavement while enhancing its appearance. By incorporating an additional carbon black polymer, RePlay+ darkens the pavement for a renewed, uniform look. Built on the trusted RePlay formula, RePlay+ delivers unmatched performance in asphalt preservation with an eco-friendly edge.

Typical Uses Asphalt highways, driveways, streets, parking lots, shoulders, trails, rumble strips, curbs. RePlay can work on **any untreated asphalt** to improve the use life and safety of the surface.

Packaging Available in 275-gallon totes and 6,600-gallon tankers

Coverage 1 tote covers 2.2 lane miles (at 0.015 gal/sq yard and 14-foot lane widths)

Key Features

Non-toxic and 77% biobased and carbon negative life cycle

Adds more than 7 new polymers to matrix

Penetrates asphalt surfaces between 3/4 and 1 1/4 inches

Protects against moisture penetration and freeze-thaw cycling stress

Maintains or improves surface traction and driver safety factor

Additional carbon black polymer enhances pavement aesthetics with a deeper, darker finish

Benefits

Biobased ensures worker and environmental safety

Improved strength and improved lifespan

Save material with precision application

Shorten traffic disruptions with rolling-lane application



Computer-Controlled Spray Rates

Fold-out Spray Wings

RePlay+ Using the Compact Spray System

General Product Specifications

Appearance	Grey to black thin liquid, slight citrus fragrance
pH	3.5-4.5
Specific Gravity	0.8820-0.8890
Flash Point	210°F+ Tag Closed Cup
Shelf Life	3 years in sealed manufacturer's container
Cure Time	Generally, cures after 60 minutes

BioSpan Spray System

- Truck-mounted, one-man operation from cab
- Computer-controlled spray rate
- Auto-adjust pressure and rate with variable speeds
- Attached spray wand for tight corners and spaces
- 8-foot main boom, 2 foldable wings to reach full 14-foot lane widths




- 5-gallon tank for product cleaner
- Product recirculation system
- Manually adjusted, easily removed from vehicle and stored

How to Use RePlay+

1. The asphalt pavement surface must be dry and swept clear of debris. Low to no visible degradation is recommended.
2. RePlay+ shall be applied as is. RePlay+ should not be diluted for any application.
3. RePlay+ must be mixed using a high shear blender in the tote before application.
4. RePlay+ is spray-applied onto highways using the BioSpan computer-controlled Spray system.
5. Application rate ranges between 0.015-0.02 gallons per square yard for pavements with PCI above 60% (in good condition).
6. Ranges may increase between 0.020-0.03 in special circumstances (rumble strips, centerline joints, oxidation)
7. Surface temperature must be above 40F.
8. RePlay+ begins curing in 30-60 minutes. RePlay+ applications may accept traffic at the discretion of the applicator.

Wear protective eyewear, gloves and close-toed shoes at all times during application. The solution is safe for both the user and the environment.



See RePlay+ in action



RePlay+ is a patented product with registered mark owned by BioSpan Technologies, Inc.

Contact Us

For more information, bulk pricing, or to place an order, contact our sales team at (800) 730-8980 or visit www.biospantech.com/replay+

