



ProTec3600 Surface Coating

Revised 12/2024

PRODUCT DESCRIPTION

ProTec3600 is specifically formulated to protect both porous and non-porous surfaces from moisture penetration, like rain and other liquids, which might stain or destroy over time.

RECOMMENDED USES

- Perfect for use on concrete, masonry, wood, and other porous or semi-porous surfaces.
- Suitable for residential, commercial, and industrial settings.

APPLICATION

- Applied as is. Do not dilute the product.
- Apply directly to the material surface
- May apply using a spray-applicator, or by brush or roller
- Apply in a smooth, even thin coating on the desired surface and allow to cure.

PRODUCT SPECIFICATIONS

Appearance	Pale yellow, clear to slightly hazy, slight orange/citrus fragrance
pH	N/A
Specific Gravity	0.9640
Flash Point	145°F+ Tag Closed Cup
Shelf Life	5 years in sealed manufacturer's container

CAUTION/LIMITATIONS

- Do not dilute.
- Always pre-mix before applying.

SURFACE PREPARATION

Make sure the surface is clear of debris or residue before applying ProTec3600. Make sure that the material is dry and retains no moisture at the time of application.

ProTec3600 is a registered mark owned by BioSpan Technologies, Inc. This information is provided "as is" and no representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information. For SDS or to consult with a BioSpan representative, call 1-800-730-8980.



ProTec3600 Surface Coating

Revised 12/2024

SAFETY/HANDLING

- Personal Protective Equipment (PPE) such as goggles, gloves and impervious clothing are recommended.
- First Aid: Refer to the Safety Data Sheet for first aid measures. Avoid inhalation and ingestion. If exposed to skin, wash with soap and water. If exposed to eyes, flush eyes immediately.

STORAGE

Store in the manufacturer's sealed container. Store in a dry, temperature-controlled environment that is well-ventilated. Do not store outside. Do not expose to high heat or freezing temperatures. To use stored product, mix for at least 30 minutes at ambient indoor temperature before application.

DISPOSAL/CLEANING

- Reactivity with water: none
- Disposal methods: Dispose of this material by incineration or by a licensed waste disposal company. Contaminated absorbent material may be disposed of in an approved landfill. Follow all local, state and Federal disposal regulations.
- Avoid contact with strong acids, strong bases and oxidizing agents. Avoid heat or an open flame.
- In Case of Spill: Floors may become slippery. Use protective equipment. Contain liquid spills using a barrier or absorb using inert material. Scoop or shovel absorbed material into containers. Wash area with soap and water.

ProTec3600 is a registered mark owned by BioSpan Technologies, Inc. This information is provided "as is" and no representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information. For SDS or to consult with a BioSpan representative, call 1-800-730-8980.